

# QUATTRO STAGIONI

**0203.**

Transpiring wall paint for interior use, high covering power

30/08/17 LRC/ib



## Description and use

QUATTRO STAGIONI is a micro porous emulsion paint based on vinyl copolymers, easy to apply, offering excellent filling properties and high hiding power.

It is recommended where a good transpirability of plasters and an excellent finish are required.

The product can be coloured using ADVANCE HT tinting system.

## Technical data

Colour	:	see catalogue
Dry film appearance	:	matt (UNI 10795)
Specific gravity	:	1.68 kg/l ( ± 0.02)
Viscosity	:	25000 ÷ 28000 mPa.s Brookfield RVT rpm 20 s 6
Classification UNI EN 13300:2002	:	Wet-scrub resistance: Class 4 (ISO 11998:2006)
	:	Hiding power: Class 2 at a spreading rate of 10 m <sup>2</sup> /l (ISO 6504-3:2007)
	:	Specular gloss: 85°, matt <10 (ISO 2813)
Practical cover rate*	:	4 ÷ 5 m <sup>2</sup> /l per two layers.
Storage life	:	24 months in original sealed container.

\*The cover rate can change depending on the surface roughness and absorption, and according to the application method.

**NB:** Data recorded @ 20°C (68°F).

The product is compliant with Directive **2004/42/CE-IIA(a)** maximum VOC limit value: 30 g/l (2010)

## Application note

Substrate preparation	:	The underlying surface must be seasoned, non-chalking and clean (no grease, oil or other polluting agents). Wherever there are damaged surfaces, remove any efflorescence and non-adhering old paints. In case of mould or algae growth, carry out a treatment with DECISO code 0610, wash the wall and, when it is completely dry, apply RENOVO code 0600. On plaster, level any unevenness with a suitable levelling compound, and allow the treated areas to rest; fill and rub down holes, cracks and crackles with IMPASTUK UNIVERSAL EXTRA code 0401, or IMPASTUK POLVERE EXTRA code 0418. On new, powdery or highly absorbing plaster, on fillings or old flaking paints, apply one layer of masonry fixative to make uniform the substrate absorption. Our suitable products are POLY VA code 0003 or POLY ACRYL code 0004, or SUPERFIX code 0010 or GREY FIX code 0011, properly reduced.
-----------------------	---	--

# QUATTRO STAGIONI

**0203.****Transpiring wall paint for interior use, high covering power**

30/08/17 LRC/ib

Once dried, continue applying two coats of QUATTRO STAGIONI.

- Product preparation : Mix to achieve even colour and consistency.
- Application method : brush - roller - air mix spray gun - airless spraying
- Dilution by volume : 35 ÷ 40% water for the first coat, 25 ÷ 30% for the second one.
- Recoatable : wait 5 ÷ 6 hours between the two coats.

**NOTE:**

Do not apply when the relative humidity exceeds 75%.

Surface and ambient temperature must be above + 5 (41°F) and below 35°C (95°F)

**BEWARE OF FROST.** Store the product between + 5 and 35°C.

Information provided in this technical data sheet is based upon our best experience and technical knowledge; it does not absolve the users from carrying out tests and preventive checks in order to verify the suitability for use. For further technical information about specific systems and/or special applications, please contact our TECHNICAL SERVICE.