

TURAPORI ALL'ACQUA

Transparent waterborne sanding sealer

0713.

14/04/16 LRC/nz

Description and use

One-component water-reducible undercoat, easy to sand and with high filling power, suitable for wood preparation before painting items exposed both indoors and outdoors (shutters and frames, furniture, matchboarding, etc.)

Technical data

Colour	:	transparent-milky
Binder	:	acrylic dispersion
Dry film appearance	:	matt
Specific gravity	:	1.01 kg/l (± 0.02)
Practical cover rate	:	8 ÷ 10 m ² /l per one coat according the type of wood.
Storage life	:	12 months in original sealed container.

NB: Data recorded @ 20°C (68°F)

The product is compliant with Directive **2004/42/CE-IIA(d)** maximum VOC limit value:130 g/l (2010)

Application note

Substrate preparation	:	Wooden surface must be dry, clean and free from oil or grease. Remove pre-existing finishes to bare wood. Apply one or two coats of TURAPORI ALL'ACQUA. After 2 ÷ 3 hours sand down the sealer, take off dust, and continue the painting using water-based finish.
Product preparation	:	Mix well to even consistency.
Application method	:	- brush - roller - spray gun with nozzle Ø 1.3 ÷ 1.5 mm and pressure of 3 ÷ 4 bar.
Reduction by weight/volume	:	10 ÷ 15% water when using a brush or roller, 15 ÷ 20% for the spray application.
Recommended thickness	:	50 ÷ 80 µm wet film 20 ÷ 40 µm dry film
Air drying @ 20°C	:	Dust free : 20 minutes Touch dry : 30 ÷ 40 minutes
Sandable	:	after 2 ÷ 3 hours

NOTE:

Max. humidity of the wood 15%.

Do not apply in foggy or rainy weather, or when the relative humidity exceeds 75%.

Surface and ambient temperature must be above + 5 (41°F) and below 35°C (95°F)

TURAPORI ALL'ACQUA

Transparent waterborne sanding sealer

0713.

14/04/16 LRC/nz

BEWARE OF FROST. Store the product between + 5 and 30°C (86°F)

Information provided in this technical data sheet is based upon our best experience and technical knowledge; it does not absolve the users from carrying out tests and preventive checks in order to verify the suitability for use. For further technical information about specific systems and/or special applications, please contact our TECHNICAL SERVICE.

This note replaces all the previous ones. Please, make sure to have the latest issue. The above mentioned data are meant to facilitate our customers in the use of our products. IMPA is not responsible for applications of products carried out beyond its direct control.

IMPA Spa - Via Crevada 9/E - 31020 San Pietro di Feletto (TV) Italy - tel. +39 0438 4548 - fax 0438 454915 - www.impa.it - info@impa.it