

PRATIK WOOD PLUS

1449.

Waxed solvent-based UV resistant thixotropic wood stain

21/05/21 rev.02



Description and use

PRATIK WOOD PLUS is a thixotropic wood stain, solvent based and matt, formulated with alkyd resins and UV filters, able to protect wood from sunrays and weathering.

The addition of water-repellent additives makes wood waterproof, avoiding water absorption, but allowing natural transpiration, to maintain wood nice and natural for a long time.

It's particularly suitable for both indoor and outdoor treatment, on fixtures, beams, balconies, doors and windows etc. The product can be coloured using ADVANCE HT tinting system.

Technical data

Colour	: transparent
Appearance after impregnating	: matt
Specific gravity	: 0.83 kg/l (± 0.02)
Practical cover rate	: 9 ÷ 12 m ² /l per one coat, according to the type of wood, the porosity and the absorption grade.
Storage life	: 24 months in original sealed container.

*May change according to the colour.

NB: Data recorded @ 20°C (68°F) and 65% RH.

The product complies with Directive **2004/42/EC**; Category **A/f**, SB: VOC max 700 g/l (2010); VOC product < 700 g/l

Application note

Substrate preparation	: Wooden surface must be dry, clean, free from oil or grease. To obtain perfect protection it's recommended to paint over PRATIK WOOD PLUS 10 hours after application with two coats of FLATTING code 1312. To protect wood just with impregnating, it's recommended to apply two coats of PRATIK WOOD PLUS and repeat the treatment every two years.
Product preparation	Stir well to even colour and consistency. To reduce the shade intensity, it is possible to mix the coloured versions with colourless PRATIK WOOD PLUS.
Application method	: brush
Reduction	: The product is ready-to-use.
Air drying (20°C - 65% RH)	: 10 ÷ 12 hours

PRATIK WOOD PLUS

1449.

Waxed solvent-based UV resistant thixotropic wood stain

21/05/21 rev.02

Information provided in this technical data sheet is based upon our best experience and technical knowledge; it does not absolve the users from carrying out tests and preventive checks in order to verify the suitability for use. For further technical information about specific systems and/or special applications, please contact our TECHNICAL SERVICE.

This note replaces all the previous ones. Please, make sure to have the latest issue. The above mentioned data are meant to facilitate our customers in the use of our products. IMPA is not responsible for applications of products carried out beyond its direct control.

IMPA S.p.A Unipersonale Via Crevada, 9/E 31020 San Pietro di Feletto (TV), Italy Tel. +39 0438 4548 Fax +39 0438 454915
Società soggetta ad attività di direzione e coordinamento di Fassa S.r.l. - info@impa.it www.impa.it