

0219 AFFRESCONITE PRO

TRANSPIRING WALL PAINT FOR INTERIOR USE, HIGH HIDING POWER, WITH FILM PROTECTED



Building



Internal



Water based



Brush



Roller



Airless



Protect from frost

Advantages

- High covering properties
- Wet-scrub resistance class 3

Description and Use

AFFRESCONITE PRO is a water-based paint for interiors with high hiding power made from polymers in aqueous emulsion. It offers a pleasant matt finish with a film protected against the growth of a wide range of mould and ensures a good breathability of the walls. It is suitable for environments with high humidity such as bathrooms, kitchens, etc.

It can be used on any properly prepared lime or lime-cement-based wall substrate finished with civil, fine mortar, gypsum, plasterboard and so on.

The product can be coloured using ADVANCE HT tinting system.

Substrate preparation

The substrate must be cured, not chalking and clean (without grease, oil or other polluting agents).

For degraded surfaces, remove all traces of old peeling paint and any efflorescence.

When there are stains, dirt and molds, perform a treatment with DECISO code 0610.

On plaster, level any unevenness with a suitable levelling compound, and allow the treated areas to rest; fill and rub down holes, cracks and crackles with IMPASTUK UNIVERSAL EXTRA code 0401.

On new, dusty or highly absorbent plaster, on render or old peeling paint, apply a layer of insulating primer to ensure uniform substrate absorption. Our suitable products are POLY ACRYL code 0004, otherwise SUPERFIX code 0010 or GREY FIX code 0011, properly diluted.

Once dried, continue applying two coats of AFFRESCONITE PRO.

