

0339 PINTOLAK MAT

WASHABLE WATER PAINT FOR INTERIORS AND EXTERIORS WITH VELVET EFFECT WITH PROTECTED FILM



Building



Interior/Exterior



Water based



Brush



Roller



Airless



Protect from frost



Advantages

- Very matt
- High yield

Description and Use

PINTOLAK MAT is a washable water-based paint based on polymers in water dispersion, with excellent covering power and good whiteness with a pleasant velvety matt appearance.

Furthermore, special additives make the film more protected from the growth of a wide range of mould.

Indoors it is suitable for any wall support such as lime-based or lime-cement finish plasters, fine mortar, gypsum, suitably prepared plasterboard

The product can be coloured using ADVANCE HT tinting system.

Substrate preparation

The substrate must be cured, not chalking and clean (without grease, oil or other polluting agents).

For degraded surfaces, remove all traces of old peeling paint and any efflorescence.

In case of mould or algae growth, carry out a treatment with DECISO code 0610.

On plaster, level any unevenness with a suitable levelling compound, and allow the treated areas to rest; fill and rub down holes, cracks and crackles with IMPASTUK UNIVERSAL EXTRA code 0401.

On new, powdery or highly absorbing plaster, on fillings or old flaking paints apply one layer of masonry fixative in order to make uniform the substrate absorption. Indoors, use the water-reducible products POLY ACRYL code 0004, or SUPERFIX code 0010 or GREY FIX code 0011, properly reduced. Outdoors, use the solvent-type ready-to-use CLIM-O-PAINT PRO code 1004, or SUPERFIX or GREY FIX.

Once dried, continue applying two coats of PINTOLAK MAT

