



1002 FONDOPAC EXTRA

SANDABLE MATT UNDERCOAT



Advantages

- Appearance matt white
- Good filler and coverage qualities

Description and Use

One-component sandable filling primer, recommended for wood preparation before painting with synthetic enamels. It can also be applied on masonry walls and hardboard.

Substrate preparation

Surface to be treated must be clean and without oil or grease stains.

When used in outdoor applications, sand the wood with abrasive P120 and carry out a pre-treatment with a coat of transparent wood stain PRATIK WOOD cod. 1441.

Once dried, continue applying two coats of FONDOPAC EXTRA.

Application

Application method:

- brush
- roller

Product preparation:

Mix to achieve even consistency.

Dilute with 1602 ACQUARAGIA: max 5%.

Storage life

If stored in a cool, dry place, away from sources of heat and sheltered from sunlight, in its sealed original packaging, the product has a shelf life of 24 months. Check the product's shelf life by referring to the production batch number shown on the packaging. The batch number is made of eight numeric characters in which the first four digits identify the year and month of production. Once the product has expired, it must be disposed of in accordance with the current legislation.

Technical features

Colour	white
Binder	alkyd resin
Appearance of the dry film	matt
Specific weight	1.71 kg/l (± 0.02)
Viscosity	50-60 seconds ISO-DIN Cup # 8
Recommended thicknesses	60-70 µm dry film (2 layers)
Practical cover rate *	5-6 m ² /l (2 layers)
Air drying (20°C - 65% RH)	30 minutes, dust-free
	2 hours, dry to touch
Sanding	after 18-24 hours
EU limit values for VOC content (Directive 2004/42/EC)	Cat. A/d. SB: max VOC 300 g/l product VOC < 300 g/l
* The cover rate is calculated on the suggested thickness and applied on plane and regular surfaces.	
The data are measured at a temperature of 20°C.	

Warnings

- Product recommended for expert users.
- It is recommended to acquire all the material required to finish the work of the same batch.
- The information provided on this technical datasheet is based on our technical and practical knowledge and experience. The technical data refer to the average characteristics of the basic product and are determined under controlled laboratory conditions. The variability of the raw materials available on the market can lead to slight deviations in the declared values, in the colour and in the aesthetic effects obtained. It is therefore necessary for the purchaser/user to personally verify, before application, the suitability of the product for the intended use, in particular when different batch numbers of the same material are used in the same work/site.

High ambient humidity and excessive thickness may delay hardening of the applied film.

The above mentioned data are meant to facilitate our customers in the use of our products. IMPA is not responsible for applications of products carried out beyond its direct control. For further technical information about specific systems and/or special applications, please contact our TECHNICAL SERVICE at assistenza.technica@impa.it.