

1020 STUCCO SINTETICO

ONE-COMPONENT SPATULA FILLER



Advantages

- Excellent adhesion
- Easy to sand

Description and Use

One-component putty based on alkyd resins, featuring excellent adhesion, good filling power and easy to sand. Suitable to be applied on wood, chip board panels and previously primed metals. Recommended to fill up small holes, cracks, surface defects. It can be overcoated with synthetic enamels for wood or metal.

Substrate preparation

Surfaces to be filled must be dry, clean and free from dust; carry out a slight sanding in order to obtain a better adhesion. Possible traces of resins, waxes or wood shining products must be carefully removed by washing with a solvent or by sanding.

Application

Application method:

- trowel

Application method:

The product is ready to use. If you want to make it smoother, thin down with little quantity of DILUENTE SINTETICO (synthetic thinner) code 1603.

Apply by spatula in thin layers exerting light pressure, in order to push the filler into the pores.

Do not apply in high thicknesses directly: when necessary, apply several subsequent thin layers, leaving a few hours in between.

Sanding:

after 24 hours.

Recoating:

just after sanding, using any kind of synthetic paint.

Storage life

If stored in a cool, dry place, away from sources of heat and sheltered from sunlight, in its sealed original packaging, the product has a shelf life of 24 months. Check the product's shelf life by referring to the production lot shown on the packaging. The lot number comprises of eight numeric characters in which the first four digits identify the year and month of production. Once the product has expired, it must be disposed of in accordance with current legislation.

Technical features

Color	white
Specific weight	1.95 kg/l (\pm 0.02)
Viscosity	130000-150000 mPa.s Brookfield rpm 20 s 10
Air drying (20°C - 65% RH)- r _per 30-40 μ m thickness	45 minutes, dust free
	2-3 hours, dry to touch
The data are measured at a temperature of 20°C.	

Warnings

- Product recommended for expert users.
- It is recommended to acquire all the material required to finish the work of the same batch.
- The information provided on this technical datasheet is based on our technical and practical knowledge and experience. The technical data refer to the average characteristics of the basic product and are determined under controlled laboratory conditions. The variability of the raw materials available on the market can lead to slight deviations in the declared values. It is therefore necessary for the purchaser/user to personally verify, before application, the suitability of the product for the intended use, in particular when different batch numbers of the same material are used in the same work/site.

The above mentioned data are meant to facilitate our customers in the use of our products. IMPA is not responsible for applications of products carried out beyond its direct control. For further technical information about specific systems and/or special applications, please contact our TECHNICAL SERVICE at assistenza.technica@impa.it.