


1402 SPEEDWAY

HIGH QUALITY TRAFFIC PAINT



Advantages

- Quick drying
- High adhesion and abrasion resistance.

Description and Use

Road marking paint which offers excellent colour retention, characterized by easy application, fast drying, high adhesion and abrasion resistance.

Product specifically developed for road markings, resistant to any type of traffic (urban, non-urban and highway).

Substrate preparation

Asphalt surface must be perfectly dry, clean, free of dust or sand.

Application

Application method:

- roller
- spray
- road marking machine

Product preparation:

Stir well to even colour and consistency.

Dilute with 1610 DILUENTE SPARTITRAFFICO at 5-10%.

Storage life

If stored in a cool, dry place, away from sources of heat and sheltered from sunlight, in its sealed original packaging, the product has a shelf life of 24 months. Check the product's shelf life by referring to the production lot shown on the packaging. The lot number comprises of eight numeric characters in which the first four digits identify the year and month of production. Once the product has expired, it must be disposed of in accordance with current legislation.

Technical features

Color	white-yellow-red-light blue
Binder	alkyd resin-chlorinated rubber
Appearance of the dry film	matt
Viscosity	2500-5000 mPa.s Brookfield rpm 20 s 4
Recommended thicknesses	120 µm dry film per coat
Estimated consumption	5 m ² /l (1 layer)
Air drying (20°C and 65% R.H.)	5 minutes, dust free
	30-40 minutes, through drying
	after about 1 hour, allowing foot traffic
AFNOR NF T 36-005 classification	Family I - Category 4a/8a
The data are measured at a temperature of 20°C.	

Warnings

- Surface and ambient temperature must be between + 10 (50°F.) and 40°C.(104°F.), and the R.H. does not exceed 75%.
- Avoid to apply in case of ice or condensation on the substrate.
- For professional use only.
- Always read the safety datasheet before use.
- Dispose of contents / container in accordance with national regulations.
- It is recommended to acquire all the material required to finish the work of the same batch.
- The information provided on this technical datasheet is based on our technical and practical knowledge and experience. The technical data refer to the average characteristics of the basic product and are determined under controlled laboratory conditions. The variability of the raw materials available on the market can lead to slight deviations in the declared values. It is therefore necessary for the purchaser/user to personally verify, before application, the suitability of the product for the intended use, in particular when different batch numbers of the same material are used in the same work/site.

The above mentioned data are meant to facilitate our customers in the use of our products. IMPA is not responsible for applications of products carried out beyond its direct control. For further technical information about specific systems and/or special applications, please contact our TECHNICAL SERVICE at assistenza.tecnica@impa.it.