

1532 ANTIROMBO

SOUND DEADENER PROTECTIVE COMPOUND,
BITUMEM-BASED



Description and Use

Protective coating based on oxidized bitumen and inert lamellar extenders.
The product is suitable for use in industrial body shop work as soundproofing compound for underside of fenders, industrial truck bottoms, car chassis, refuse containers, doors and windows metal fittings, etc.
It can be also applied on underground tank and pipes.

Substrate preparation

Surfaces must be dry, clean, dust free and made slightly rough by sanding.
Product can be applied directly on bare steel sheet or over a primer.

Application

Application method:

- special spry gun for sound deader compound at 3-4 bar pressure, operating at 20 cm. approx. from surface.

The greater or lesser texture can be obtained varying the air pressure.
Dilute with DILUENTE NITRO ANTINEBBIA (cellulose thinner) code 1616, to obtain a more smooth textured surface.

Storage life

If stored in a cool, dry place, away from sources of heat and sheltered from sunlight, in its sealed original packaging, the product has a shelf life of 12 months. Check the product's shelf life by referring to the production lot shown on the packaging. The lot number comprises of eight numeric characters in which the first four digits identify the year and month of production. Once the product has expired, it must be disposed of in accordance with current legislation.

Technical features

Color	black
Binder	bituminous
Appearance of the dry film	semigloss, slightly textured
Total non-volatile by weight	81% (± 1)
Specific weight	1.51 kg/l (± 0.02)
Viscosity	40000-50000 mPa.s Brookfield rpm 10 s 6
Indicative actual yield	3-4 m ² /kg referred to thickness of 200-300 μ m
Air drying (20°C - 65% RH)	1 hour. dust-free
	24 hours, through drying
Recoatable	not overcoatable
EU limit values for VOC content (Directive 2004/42/EC)	Category B/e: VOC max 840g/l product VOC < 840g/l
The data are measured at a temperature of 20°C.	

Warnings

- For professional use only.
- Always read the safety datasheet before use.
- Dispose of contents / container in accordance with national regulations.
- It is recommended to acquire all the material required to finish the work of the same batch.
- The information provided on this technical datasheet is based on our technical and practical knowledge and experience. The technical data refer to the average characteristics of the basic product and are determined under controlled laboratory conditions. The variability of the raw materials available on the market can lead to slight deviations in the declared values. It is therefore necessary for the purchaser/user to personally verify, before application, the suitability of the product for the intended use, in particular when different batch numbers of the same material are used in the same work/site.

High environment humidity and excessive thickness may retard the hardening of the applied film.

The above mentioned data are meant to facilitate our customers in the use of our products. IMPA is not responsible for applications of products carried out beyond its direct control. For further technical information about specific systems and/or special applications, please contact our TECHNICAL SERVICE at assistenza.technica@impa.it.