


1901 ADDITIVO AGGRAPPANTE PER VETRO



Advantages

→ It increases the adhesion of paint products on glass.

Description and Use

Additive to be used to increase the adhesion of two-component paint products to glass. Add immediately before application to part A of the product.

Substrate preparation

- The surface must be free from dust and/or dirt etc.
- Taking into consideration the variability of the supports it is recommended to test previously the performance.

Application

Use at 10% by weight, compensating for the amount of thinner to be added. The additive must be added to the following products according to the instructions given in the respective technical data sheets:

- 1960 AGRIL-COAT DUO LUCIDO
- 1961 AGRIL-COAT DUO OPACO
- 1736 FONDO FINITURA ACRILICO OPACO DTM
- 1836 FONDO FINITURA ACRILICO SEMI OPACO DTM
- 1949 FONDO FINITURA ACRILICO SEMI LUCIDO DTM
- 1924 AGRIL-PU TIXO LUCIDO
- 1925 AGRIL-PU TIXO OPACO

Storage life

If stored in a cool, dry place, away from sources of heat and sheltered from sunlight, in its sealed original packaging, the product has a shelf life of 12 months. Check the product's shelf life by referring to the production batch number shown on the packaging. The batch number is made of eight numeric characters in which the first four digits identify the year and month of production. Once the product has expired, it must be disposed of in accordance with the current legislation.

Technical features

Colour	Transparent
Specific weight	0.87 kg/l (±0,02)
The data are measured at a temperature of 20°C.	

Warnings

- For industrial use only.
- Always read the safety datasheet before use.
- Dispose of contents / container in accordance with national regulations.
- You should perform a preliminary application test.
- Keep dry. Close the container carefully after opening to preserve the characteristics of the product.
- It is recommended to acquire all the material required to finish the work of the same batch.
- The information provided on this technical datasheet is based on our technical and practical knowledge and experience. The technical data refer to the average characteristics of the basic product and are determined under controlled laboratory conditions. The variability of the raw materials available on the market and the tinting of the product can lead to slight deviations in the declared values, in the colour and in the aesthetic effects obtained. It is therefore necessary for the purchaser/user to personally verify, before application, the suitability of the product for the intended use, in particular when different batch numbers of the same material are used in the same work/site.

The above mentioned data are meant to facilitate our customers in the use of our products. IMPA is not responsible for applications of products carried out beyond its direct control. For further technical information about specific systems and/or special applications, please contact our TECHNICAL SERVICE at assistenza.technica@impa.it.