

2015 ZINCO CHIARO SPRAY

LIGHT GREY ZINC COATING PRIMER



Car refinish



Ready-to-use



Shake before use

Description and Use

One-component cold galvanizing primer characterized by fast drying, good corrosion resistance and high hiding power.

Substrate preparation

Surfaces must be dry, clean, dust free and made slightly rough by sanding.

Application

Application method:

- Spray at 20-25 cm from surface.

Product preparation:

Shake the can thoroughly for 3 minutes before using it.

Recommended thicknesses:

20-30 μm .

Apply 2 or 3 thin layers with an interval of 10 minutes between coats.

Recoating:

Between 24 and 48 hours.

Storage life

If stored in a cool, dry place, away from sources of heat and sheltered from sunlight, in its sealed original packaging, the product has a shelf life of 30 months. Check the product's shelf life by referring to the production lot shown on the packaging. The batch code is made up of eight alphanumeric characters, the first two digits indicate the year and the following three the Julian day of production. For example, in the code ST23195Z the number 23 indicates the year and 195 the Julian day on which production took place. Once the product has expired, it must be disposed of in accordance with current legislation.

Technical features

Colour	light grey
Binder	aklky modified
Indicative actual yield	1.1-1.4 m ² per one spray can, according to the applied thickness.
Air drying	30-45 minutes. dust-free
	2-3 hours, dry to touch
	6-8 hours, through drying
EU limit value of VOC content (Directive 2004/42/EC)	Category B/e, SB: VOC max 840g/l product VOC < 840g/l
The data are measured at a temperature of 20°C and 65% R.H.	

Warnings

- For professional use only.
- Always read the safety datasheet before use.
- Dispose of contents / container in accordance with national regulations.
- It is recommended to acquire all the material required to finish the work of the same batch.
- The information provided on this technical datasheet is based on our technical and practical knowledge and experience. The technical data refer to the average characteristics of the basic product and are determined under controlled laboratory conditions. The variability of the raw materials available on the market can lead to slight deviations in the declared values. It is therefore necessary for the purchaser/user to personally verify, before application, the suitability of the product for the intended use, in particular when different batch numbers of the same material are used in the same work/site.

The above mentioned data are meant to facilitate our customers in the use of our products. IMPA is not responsible for applications of products carried out beyond its direct control. For further technical information about specific systems and/or special applications, please contact our TECHNICAL SERVICE at assistenza.technica@impa.it.