

2204 PHASE 1

POLISHING CREAM



Advantages

- Remove any marks or rings after the polishing phase.
- It eliminates paint fumes (overspray).

Description and Use

Creamy mixture of medium-fine abrasives specific for the treatment of bodywork paints. It eliminates paint fumes (overspray), speckling and small scratches. Ideal for removing marks caused by microabrasives. It restores the shininess of the old or opacified paintwork.

Substrate preparation

Surfaces to be treated must be dry, clean and dust free.
Avoid hot media.

Suitable surfaces:

- Hardened varnishes.

For further information apply to our TECHNICAL SERVICE.

Application

Application method:

- Shake before use.
- Pour the product of medium density foam pad.
- Apply the product with electric polisher at low speed, and gradually increased to make the support properly polished.
- For more evident defects using a harder swab.
- Any excess product can be removed with a microfiber cloth and QUICK OFF cod. 0642.
- Then treat the surface with POLISH EXTRA GLOSS cod. 2201 to obtain a full gloss.

Storage life

PROTECT FROM FROST. Surface and ambient temperature must be above + 5 (41°F) and below 30°C (86°F). If stored in a cool, dry place, away from sources of heat and sheltered from sunlight, in its sealed original packaging, the product has a shelf life of 24 months. Check the product's shelf life by referring to the production batch number shown on the packaging. The batch number is made of eight numeric characters in which the first four digits identify the year and month of production. Once the product has expired, it must be disposed of in accordance with current legislation.

Technical features

Colour	white
Physical state	creamy-liquid

Warnings

- For professional use only.
- Always refer to the safety data sheet for the relevant products.
- Solvents or thinners used for cleaning tools, as well as any product residues, must not be released into the environment or poured down domestic drains. The recipient/product/thinner or cleaning solvent must be disposed of in accordance with national regulations.
- NOTE: Do not apply in foggy or rainy weather, or when the relative humidity exceeds 75%.
- Surface and ambient temperature must be above + 5 (41°F) and below 30°C (86°F).
- The information provided on this technical datasheet is based on our technical and practical knowledge and experience. The technical data refer to the average characteristics of the basic product and are determined under controlled laboratory conditions. The variability of the raw materials available on the market can lead to slight deviations in the declared values. It is therefore necessary for the purchaser/user to personally verify, before application, the suitability of the product for the intended use, in particular when different batch numbers of the same material are used in the same work/site.

The above mentioned data are meant to facilitate our customers in the use of our products. IMPA is not responsible for applications of products carried out beyond its direct control. For further technical information about specific systems and/or special applications, please contact our TECHNICAL SERVICE at assistenza.technica@impa.it.