



DECLARATION OF PERFORMANCE

N.0638-CPR-26-01

1. Unique identification code of the product-type: **ELASTO WALL**
2. Intended uses: **Coating for intended use in concrete surface protection by protection against ingress, moisture control and increasing resistivity method**
3. Manufacturer: **IMPA S.p.A. Unipersonale - Via Crevada, 9/E - 31020 San Pietro di Feletto (TV), Italy**
4. Authorised representative: Not applicable
5. Systems of Assessment and Verification of Constance of Performance (AVCP): **4**
6. Harmonised standard: **EN 1504-2:2005**
7. Declared performances

Water vapour permeability	Class I
Capillary absorption and permeability to water	< 0,1 kg/m²·h^{0,15}
Resistance to cracking	Class A2 (23°C); A1 (-10°C)

Permeability to CO ₂	Sd > 50 m
Adhesion strength by pull-off test	≥ 0,8 N/mm²
Reaction to fire	E
Dangerous substances	See MSDS

8. Not applicable

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) n.305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Cristiano Marchesin

General manager

S. Pietro di Feletto (TV), 20/01/2026

ELASTO WALL



IMPA S.p.A. Unipersonale

Via Crevada, 9/E

31020 San Pietro di Feletto (TV), Italy

23

0638-CPR-26-01

EN 1504-2:2005

ELASTO WALL

**Coating for intended use in concrete surface protection by
protection against ingress, moisture control and increasing
resistivity method**

Water vapor permeability: Class I

**Capillary absorption and
permeability to water:** $< 0,1 \text{ kg/m}^2 \cdot \text{h}^{0,5}$

Resistance to cracking Class A2 (23°C); A1 (-10°C)

Permeability to CO2: $S_d > 50 \text{ m}$

**Adhesion strength by pull-off
test:** $\geq 0,8 \text{ N/mm}^2$

Reaction to fire: E

Dangerous substances: See MSDS